

Searching for **breakpoint and remove**.

Restrict to: [Header](#) [Title](#) Order by: [Citations](#) [Hubs](#) [Usage](#) [Date](#) Try: [Amazon](#) [B&N](#) [Google \(RI\)](#) [Google \(Web\)](#) [CSB](#) [DBLP](#)

26 documents found. Order: citations weighted by year.

[SICStus Prolog User's Manual - Laboratory \(2001\)](#) (Correct) (8 citations)

never existed. advice-point A special case of **breakpoint**, the advice **breakpoint**. It is distinguished  
A special case of **breakpoint**, the advice **breakpoint**. It is distinguished from spypoints in that it  
[www.sics.se/sicstus/docs/latest/pdf/sicstus.pdf](http://www.sics.se/sicstus/docs/latest/pdf/sicstus.pdf)

[Fine-Grained Dynamic Instrumentation of Commodity Operating.. - Tamches, Miller \(1999\)](#) (Correct) (17 citations)

using finegrained dynamic instrumentation. **Breakpoints** can be inserted at any machine code  
thread and informs the debugger. Conditional **breakpoints** are easily accommodated by predicating the  
reached. Instrumentation for a basic block can be **removed** as soon as the flag is set thus, the overhead  
[www.cs.wisc.edu/paradyn/papers/kerninst.ps.gz](http://www.cs.wisc.edu/paradyn/papers/kerninst.ps.gz)

[Breakpoint Phylogenies - Mathieu Blanchette Guillaume \(1997\)](#) (Correct) (12 citations)

**Breakpoint** Phylogenies Mathieu Blanchette Guillaume

optimization criterion is the minimum number of **breakpoints** (pairs of genes adjacent in one genome but not  
-2, set up TSP for G M solve TSP for G M **remove** the two neighbors of VM preceding it in the  
[www.cs.washington.edu/homes/blanchem/papers/GIW97/giw97.ps](http://www.cs.washington.edu/homes/blanchem/papers/GIW97/giw97.ps)

[A Retargetable Debugger - Ramsey \(1992\)](#) (Correct) (18 citations)

the expressions. Debugging tasks like planting **breakpoints** and walking the call stack have no analogs in  
lines from the VAX nub, and the formalization of **breakpoint** commands mentioned in Section 7.7 is his idea.  
[www.eecs.harvard.edu/~nr/pubs/thesis.ps.gz](http://www.eecs.harvard.edu/~nr/pubs/thesis.ps.gz)

[Practical Data Breakpoints: Design and Implementation - Robert Wahbe \(1993\)](#) (Correct) (14 citations)

Practical Data **Breakpoints**: Design and Implementation Robert Wahbe y

UC Berkeley, Berkeley CA, 94720 Abstract A data **breakpoint** associates debugging actions with  
Second, we use data flow analysis techniques to **remove** checks on write instructions within loops. We  
[www.cag.lcs.mit.edu/~mfrank/collect/wahbe\\_lucco\\_graham\\_pldi93.ps.gz](http://www.cag.lcs.mit.edu/~mfrank/collect/wahbe_lucco_graham_pldi93.ps.gz)

[Experimental And Statistical Analysis Of Sorting By Reversals - Caprara, Lancia \(2000\)](#) (Correct) (2 citations)

reversals and show how the expected number of **breakpoints** changes with the number of reversals applied.  
some random variables such as X ,the number of **breakpoints**, Y ,the number of reversals applied by  
branch and bound procedure. Since a reversal can **remove** at most two **breakpoints**, and has no  
[www.dei.unipd.it/~lancia/psdir/dcaf.ps.gz](http://www.dei.unipd.it/~lancia/psdir/dcaf.ps.gz)

[An Easy Case of Sorting by Reversals - Tran \(1997\)](#) (Correct) (5 citations)

in polynomial time, namely, when the number of **breakpoints** is twice the distance. Keywords: sorting by  
reversal distances are twice the number of "**breakpoints**"which are boundaries between blocks of  
for We already observed that each ae i must **remove** a pair of **breakpoints**. The following lemma says  
[www.cs.twsu.edu/~tran/papers/reversals.ps](http://www.cs.twsu.edu/~tran/papers/reversals.ps)

[A Machine-Independent Debugger - David Hanson And \(1995\)](#) (Correct) (5 citations)

to lcc's front end to emit symbol tables and **breakpoint** hooks. All this code is machine independent.  
hardware-specific facilities for implementing **breakpoints** and single stepping. Debuggers depend on  
terminates. Nub\_set and \_Nub\_remove set and **remove breakpoints**. Debuggers must implement higher  
[www.cs.princeton.edu/~drh/pubs/cdb.pdf](http://www.cs.princeton.edu/~drh/pubs/cdb.pdf)

[Bisection Debugging - Gross \(1997\)](#) (Correct) (2 citations)

that there are no constraints on where a **breakpoint** can be set, and the debugger must be able to  
be able to solve all data value problems at this **breakpoint**. The quality of the file differencing program  
version of the compiler or runtime system, to **remove** bugs for some input sets, etc. When such changes  
[www.ep.liu.se/ea/cis/1997/009/15/cis9700915.ps](http://www.ep.liu.se/ea/cis/1997/009/15/cis9700915.ps)

High-Performance Protocols for Clusters of Commodity Workstations - Melas, Zaluska (1998) (Correct) (1 citation)  
of the high-performance switch (TB2/TB3)The **breakpoint** at 4 KB on the SP2 graph is due to the change  
MPPs. Then for messages up to 4KB (which is the **breakpoint** of the SP2 at Argonne)the SP2 has a higher  
which avoid routing through the kernel can **remove** this limit on communication performance and  
[www.ecs.soton.ac.uk/~pm95r/my\\_papers/euopar98.ps](http://www.ecs.soton.ac.uk/~pm95r/my_papers/euopar98.ps)

Optimal Multi-Paragraph Text Segmentation by Dynamic Programming - Heinonen (1998) (Correct) (1 citation)  
and all the possible locations of the previous **breakpoint** are considered. We continue this procedure till  
the text, and finally we can generate a list of **breakpoints** that indicate the fragmentation. The cost at  
similarities as follows. We employ stemming, **remove** stopwords, and count the frequencies of the  
[www.csi.uottawa.ca/tanka/ArtDB/oh\\_ca98.ps](http://www.csi.uottawa.ca/tanka/ArtDB/oh_ca98.ps)

Optimal Multi-Paragraph Text Segmentation by Dynamic.. - University Of Helsinki (Correct)  
and all the possible locations of the previous **breakpoint** are considered. We continue this procedure till  
the text, and finally we can generate a list of **breakpoints** that indicate the fragmentation. The cost at  
similarities as follows. We employ stemming, **remove** stopwords, and count the frequencies of the  
[acl.ldc.upenn.edu/P/P98/P98-2244.pdf](http://acl.ldc.upenn.edu/P/P98/P98-2244.pdf)

Genome Rearrangements and Sequencing By Hybridization - Hartman (2001) (Correct)  
rearrangements literature is the notion of **breakpoint**. A pair of elements  $(i \ i \ 1)$  is called a  
A pair of elements  $(i \ i \ 1)$  is called a **breakpoint** if  $i \setminus \Gamma \Gamma \ 1 = 1$  (for unsigned  
Work 1.3.1 Reversal Distance A reversal can **remove** at most two **breakpoints** in a permutation.  
[www.wisdom.weizmann.ac.il/~tzvi/papers/prop.ps](http://www.wisdom.weizmann.ac.il/~tzvi/papers/prop.ps)

Analysis of Hardware and Software Approaches to Embedded.. - Chen, Kao, Huang (Correct)  
registers/memory, single stepping, setting **breakpoints**. The development system diagram is shown in  
Downloader Debug Software Download Program Set **Breakpoint** Control Command (Go,Stop,Step,Breakpoint) Dump  
phase of the SoC chip. There is no way to **remove** it out of the SoC chip. Therefore, the  
[www.jrpit.flinders.edu.au/confpapers/CRPITV6Chen.pdf](http://www.jrpit.flinders.edu.au/confpapers/CRPITV6Chen.pdf)

Is There an Optimal Structure for Decentralized Provision.. - Humplick, Moini-Araghi (Correct)  
percent. The debt crisis could have been a major **breakpoint** for the transfer of responsibilities to lower  
standards combined with decentralized maintenance **remove** the incentive to reduce costs and erode most of  
q. The costs are expressed in \$per km in order to **remove** effects of scale 7 and are allowed to vary by the  
[econ.worldbank.org/files/667\\_wps1657.pdf](http://econ.worldbank.org/files/667_wps1657.pdf)

M68hc12b32evb - User's Manual October (Correct)  
. 52 BR **Breakpoint** Set .  
. 78 NOBR **Remove Breakpoints** .  
. 78 NOBR **Remove Breakpoints** .  
[egweb.mines.edu/eggn482/labs/evbmanual.pdf](http://egweb.mines.edu/eggn482/labs/evbmanual.pdf)

Reconstructing an Ancestral Genome Using Minimum Segments.. - El-Mabrouk (Correct)  
compared according to a variety of criteria. The **breakpoint** distance between two genomes G and H measures  
G. Moreover, as a reversal can act on only two **breakpoints**, it is clear that a reversal can not decrease  
is the exemplar approach [San99]The idea is to **remove** all but one member of each gene family in each of  
[www.iro.umontreal.ca/~mabrouk/publications/dupliFragments.ps](http://www.iro.umontreal.ca/~mabrouk/publications/dupliFragments.ps)

Finding an Optimal Inversion Median: Experimental Results - Siepel, Moret (2001) (Correct)  
In addition, we have compared inversion and **breakpoint** medians, and found that inversion medians  
genomes. These studies have generally used **breakpoint** distance as the basis for finding medians,  
is related to inversion distance (an inversion can **remove** at most two **breakpoints**) but the relationship is  
[www.cs.unm.edu/~moret/invmedian.ps](http://www.cs.unm.edu/~moret/invmedian.ps)

Improved Bicriteria Existence Theorems for Scheduling - Aslam, Rasala, Stein, Young (1999) (Correct)  
any average completion time schedule (pdf)the **breakpoint** that gives the best bicriteria result this  
and consider the schedule formed by having a **breakpoint** at #L. The jobs that complete before time #L  
First, if we take a valid schedule S and **remove** from it all jobs that complete after time t, the  
[www.cs.dartmouth.edu/~cliff/papers/BicriteriaSoda.ps.gz](http://www.cs.dartmouth.edu/~cliff/papers/BicriteriaSoda.ps.gz)

First 20 documents Next 20

Try your query at: [Amazon](#) [Barnes & Noble](#) [Google \(RI\)](#) [Google \(Web\)](#) [CSB](#) [DBLP](#)  
CiteSeer - [citeseer.org](http://citeseer.org) - [Terms of Service](#) - [Privacy Policy](#) - Copyright © 1997-2002 [NEC Research Institute](#)

Searching for **breakpoint and remove**.

Restrict to: [Header](#) [Title](#) Order by: [Citations](#) [Hubs](#) [Usage](#) [Date](#) Try: [Amazon](#) [B&N](#) [Google \(RI\)](#) [Google \(Web\)](#) [CSB](#) [DBLP](#)

26 documents found. Order: citations weighted by year.

[FIRST: A Framework for Interoperable Resources, Services, and.. - Prodan, Kewley \(Correct\)](#)  
constructs, such as: set/increment counter, set **breakpoint** and insert timer. Extensibility: By defining of the application, viewing variables and adding **breakpoints**. Development of such tools is comparatively instrumentation ffl add instrumentation to (and **remove** it from) the attached application process at any [www.cscs.ch/~kewley/pubs/PDPTA99.ps.gz](http://www.cscs.ch/~kewley/pubs/PDPTA99.ps.gz)

[A Machine-Independent Debugger - Revisited - Hanson \(Correct\)](#)  
of a stopped target, which occurs at start-up, **breakpoints**, and faults. Nub\_set, Nub\_remove, and and \_Nub\_src collaborate to implement **breakpoints**. Stopping points define program locations at point, Nub\_set sets a **breakpoint**, and \_Nub\_remove removes one. When a **breakpoint** occurs, the **breakpoint** [www.research.microsoft.com/~drh/pubs/cdb3.pdf](http://www.research.microsoft.com/~drh/pubs/cdb3.pdf)

[PanParallacea: a System for Debugging and Monitoring Parallel.. - Moe \(Correct\)](#)  
: 115 9.2 **Breakpoint** Debuggers  
operating systems 14 4.6.1 Evaluation **Breakpoints** make sense in data-parallel programs, enabling of how to monitor performance, isolate errors, and **remove** bugs. We then describes the state of the art of [www.idi.ntnu.no/IDT/grupper/DB-grp/tech\\_papers/moe92.ps](http://www.idi.ntnu.no/IDT/grupper/DB-grp/tech_papers/moe92.ps)

[Intelligent Support for Problem Formalisation in Design - Martin Dzbor Knowledge \(1999\) \(Correct\)](#)  
the suggested alternative solutions and the key **breakpoint** came when they looked at the rack as 'a tray' subsequent refinements of that approach did not **remove** a principal issue of mud spray thrown by the new formulations. This inconsistency might be **removed** by introduction of another mapping type. Let us [kmi.open.ac.uk/people/dzbor/public/1999/dzbor-ines99.pdf](http://kmi.open.ac.uk/people/dzbor/public/1999/dzbor-ines99.pdf)

[TOPAL 2.0: Improved graphical method and statistical test for .. - McGuire, Wright \(Correct\)](#)  
in a data set. This test can find recombination **breakpoints** but can only be applied to a maximum of four find recombination events: the former can detect **breakpoints** but is computationally intensive and requires the definition of the Dss statistic which should **remove** much of the confounding between rate variation [www.rdg.ac.uk/~sns98gm/dss.ps](http://www.rdg.ac.uk/~sns98gm/dss.ps)

[Visualization, Execution Control and Replay of.. - Cl  men  on, Fritscher.. \(1995\) \(Correct\)](#)  
debugging: execution control (handling of **breakpoints**, watchpoints, and exceptions)distributed global views to distributed arrays and different **breakpointing** mechanisms, for instance to allow for hits a **breakpoint**, and the user can set or **remove** a **breakpoint** by clicking the mouse on the desired [ftp.cscs.ch/pub/CSCS/papers/HPCS95.ps.gz](http://ftp.cscs.ch/pub/CSCS/papers/HPCS95.ps.gz)

[Documents 21 to 26](#) [Previous 20](#)

Try your query at: [Amazon](#) [Barnes & Noble](#) [Google \(RI\)](#) [Google \(Web\)](#) [CSB](#) [DBLP](#)

CiteSeer - [citeseer.org](http://citeseer.org) - [Terms of Service](#) - [Privacy Policy](#) - Copyright    1997-2002 NEC Research Institute